



**The G3-070 Anti-Slip/Step Edge Contrast is designed to both define the step edge and help prevent slips and falls in all weather conditions.**

**PERFORMANCE**

G3-070 is suitable for use indoors and outdoors. The anti-slip material provides all weather protection from slips and falls.

**Anti-slip Properties –**

UL410 Standard for Slip Resistance for Floor Surface Materials  
AS/NZS 4586-2004 Classification: Dry: F Wet: V Ramp: R12  
AS 4586-2013 Classification: P5

**Salt Spray Resistance –** ASTM B117: Pass

**Washability –** ASTM D4828: Pass

**Rate of Burning –** ASTM D635: Pass

**Surface Flammability –** ASTM E162: Pass

**Toxicity –** Bombardier Toxic Gas Generation Test SMP800-C: Pass

**Radioactivity –** ASTM D3648: Pass

**High Temperature Curing:** Pass

**SUPPLY**

The product is available in 3.06 metre lengths.

**COMPOSITION**

Ecoglo G3-070 is manufactured from extruded 60605T aluminium section. Silicon Carbide anti-slip materials are embedded in thermoset polyester carriers to integrally bond the active ingredients into the aluminium following curing at high temperature.



**INSTALLATION**

Indoors G3-070 can be surface mounted on all smooth surfaces. Outdoors G3-070 can be surface mounted onto concrete.

Maximum recommended length for outdoor installation is 1500mm.

Installation needs to be carried out strictly in accordance with the Ecoglo installation instructions.

Consult Installation Instructions on website for full details and surface preparation.

Screws can be used if adhesion is difficult.

**G3-070-3060** For polyurethane adhesive fixing

*Contact*

**Ecoglo Fire Protection Product Trading**

**Address:** 36-C Gloria Street, Barangay San Carlos, Binangonan Rizal 1940, Philippines

**Office:** +632-8802-4760

**Cell:** +63917-514-6803

+63968-356-4773

**Email:** keith.phillips@ecoglo.com

**Web:** www.ecoglo.ph www.EcogloAsia.com www.EcogloVenues.com