

Product Data Sheet - S5 Directional Exit Right and Left EXRL-BFP

2024 V2


VISIBLY BETTER



Ecoglo S5 Directional "Exit Right and Left" Signs are designed to meet the Directional sign requirements of Section 10.2.5.12 Clause A(6) and the text size requirements of Section 10.2.5.12 Clause C of the Fire Code of the Philippines.

SIGN DEFINITION

Exit right and left from here.

COMPLIANCE

Ecoglo S5 Directional "Exit Right and Left" Signs require a minimum of 54 lux on the face of the sign 60 minutes prior to, and during, occupancy of the building for use under section 10.2.5.12 Clause A(6).

Luminance - S5 grade signs easily exceed PSPA Class D.

UV Resistance - Loss of luminance after 1000 hrs ASTM G-155 Cycle 1 exposure: <10%

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass

Rate of Burning – ASTM D635: Pass

Surface Flammability - ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

High Temperature Curing: Pass

Operating Temperature Range: +10°C to +30°C

SUPPLY

Ecoglo S5 Directional Exit Right and Left Sign consists of an Ecoglo S5 Directional Exit Right Sign and an Ecoglo S20 Chevron. The product is available in 2 sizes - maximum viewing distance 16 metres and maximum viewing distance 24 metres.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE	MAXIMUM VIEWING DISTANCE
S5-BFP3416RL-16m	Exit Right and Left	Exit Right and Left from here	340mm x 162mm	16 metres
S5-BFP4923RL-24m	Exit Right and Left	Exit Right and Left from here	490mm x 230mm	24 metres

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature.



INSTALLATION

The 2 piece sign is supplied with fixers for mounting flat on a wall.

Contact

Ecoglo Customer Service

Email: InfoPHL@ecoglo.com

Customer Service Cell: +63 917 545 0090 (call / text / whatsapp / viber)

Operations & Administration Landline: +63 2 8802 4760

Website: www.ecoglo.ph