
Product Data Sheet - Step Edge Contrast N15-080









The N15-080 Step Edge Contrast is designed to both define the step edge and help prevent slips and falls in all weather conditions.

PERFORMANCE

The Step Edge Contrast is suitable for use indoors and outdoors. The anti-slip material provides all weather protection from slips and falls.

Anti-slip Properties -

UL410 Standard for Slip Resistance for Floor Surface Materials AS/NZS 4586-2004 Classification: Dry: F Wet: V Ramp: R12 AS 4586-2013 Classification: P5

Salt Spray Resistance – ASTM B117: Pass

Washability - ASTM D4828: Pass

Rate of Burning - ASTM D635: Pass

Surface Flammability - ASTM E162: Pass

Toxicity – Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

The product is available in 100mm increments from 800mm to 1500mm. Custom lengths can also be fabricated on site from 2.45 metre and 3.06 metre lengths.

COMPOSITION

Ecoglo N15-080 Step Edge Contrast is manufactured from extruded 6063T5 aluminium section. Silicon Carbide and/or aluminium oxide antislip materials are embedded in thermoset polyester carriers to integrally bond the active ingredients into the aluminium following curing at high temperature.

INSTALLATION

Indoors the N15-080 Step Edge Contrast can be surface mounted on all smooth surfaces. Outdoors the N15-080 can be surface mounted onto concrete.

Maximum recommended length for outdoor installation is 1500mm.

Installation needs to be carried out strictly in accordance with the Ecoglo installation instructions.

Consult Installation Instructions on website for full details and surface preparation.

Screws can be used if adhesion is difficult. (See order codes below for the product that best suits).

N15-080 For polyurethane adhesive fixing N15-080P Punched for screw fixing

PRODUCT CODE	PRODUCT DESCRIPTION	PRODUCT LENGTH
N15-080-800	Step Edge Contrast 64mm	800mm
N15-080-900	Step Edge Contrast 64mm	900mm
N15-080-1000	Step Edge Contrast 64mm	1000mm
N15-080-1100	Step Edge Contrast 64mm	1100mm
N15-080-1200	Step Edge Contrast 64mm	1200mm
N15-080-1300	Step Edge Contrast 64mm	1300mm
N15-080-1400	Step Edge Contrast 64mm	1400mm
N15-080-1500	Step Edge Contrast 64mm	1500mm

Contact

Ecoglo Fire Protection Product Trading

Address: 36-C Gloria Street, Barangay San Carlos,

Binangonan Rizal 1940, Philippines

Office: +632-8802-4760 Cell: +63917-514-6803 +63968-356-4773 Email: keith.phillips@ecoglo.com

Web: www.ecoglo.ph www.EcogloAsia.com www.EcogloVenues.com